Smart Choices in Hydrotropes Institutional & Industrial Cleaning

Hydrotropes are deployed in various liquid cleaners to increase the solubility of surfactant in concentrated formulation and thus improve the stabilities.

BASF offers a series of hydrotropes fitting different performance requirement in different institutional & industrial cleaning applications.



Product & Application Guide

Product	Feature	Active matter	Biodegradability	Primary Applications				
				CIP	COP	C.Laundry	Rinse Aid	HSC*
Glucopon® 101LF	Alkyl Polyglycoside	Approx. 62%	+++	1				
Glucopon® 225 DK	Caprylyl/Decyl Polyglycoside	Approx. 70%	+++	1				
Disponil® EHS 47	Sodium Etasulfate	Approx. 47%	+++					
Deriphat® 160C	Amphoteric	Approx. 30%	+++	2				
Lutensol® CS 6250	Alcohol Ethoxylate	Approx. 100%	++	2				

CIP: Clean-In-Place

COP: Cleaning out of Place

C. Laundry: Commercial Laundry

* HSC: Hard surface cleaning (incl. Degreaser)

+++: Readily Biodegradable by OECD criteria (≥60% in 10-day window)

++: Readily biodegrabdable (≥60% in 28 days) | ¹Alkaline CIP | ²Acidic CIP



Foam profile and alkaline tolerance

Surfactants generate foam with motions in the system. Low Foaming surfactant is designed particularly for CIP cleaning and rinse aid in Auto Dishwash. However, COP cleaning requires high foaming ability of cleaners to cover the surface for efficient cleaning.

Product		am Height (n es (0.1% wt	Maximium Alkaline tolerance (Hydrotrope	
	0 min	30 sec	5 min	dosage :5% active)
Glucopon® 101LF	20	0	0	20%
Glucopon® 225 DK	370	320	300	30%
Disponil® EHS 47	45	40	30	10%
Deriphat® 160 C	170	130	110	20%
Lutensol® CS 6250	40	10	5	N/A


Hydrotrope Power

Proper hydrotropes ensure clear liquid formulation under different PH range, especially when the surfactant concentration increases, the consequent turbity cause operational issues.

Neutral: (90% water, 5% hydrotrope) + Plurafac LF 403 until turbid

Alkaline: (75% water, 10% NaOH , 5 % hydrotrope) + Plurafac LF 403 until turbid

Acidic: (75% water, 10% Lutropur MSA, 5% hydrotrope) + Plurafac LF 403 until turbid




Viscosity management

Tested formulation

Lutensol® A7N	50%
Plurafac® LF 403	5%
Hydrotrope	5% (active)
Water	to 100%

Viscosity of tested formulation



Viscosity: Brookfield, 60 rpm [mPa.s], 23º C

Rinse aid for Auto Dishwash (Cloud point: 40°c)

Hydrotrope (wt.%)	P	Pluronic® Types		
· · ·	LF 221 10% LF 403 5%	LF221 10% LF 305 5%	LF 300 10% LF 403 5%	PE 6200 10% PE6100 5%
Disponil® EHS 47	2.16	1.08	4.67	3.94
Lutensit® SCS 40	3.98	1.32	6.34	12.06

BASF Care Chemical Home Care and I&I Solutions

BASF East Asia Regional Headquarters Limited 45/F Jardine House No. 1 Connaught Place Central, Hong Kong <u>detergents-cleaners-hk@basf.com</u>

https://www.homecare-and-i-and-i.basf.com/asiapacific

Safety We know of no ill effects that could have resulted from using our products for the purpose for which they are intended and from processing them in accordance with current practice. According to the experience we have gained up to now and other information at our disposal, our products do not exert any harmful effects on health, provided that they are used properly, due attention is given to the precautions necessary for handling chemicals, and the information and advice given in our safety data sheets are observed. Details about the classification and labeling of our products and further advice on safe handling are contained in the current safety data sheets. Note This document, or any answers or information provided herein by BASF, does not constitute a legally binding obligation of BASF. While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It does not relieve our customers from the obligation to perform a full inspection of the products upon delivery or any other obligation. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE.

